

Leica NA300 Series



Leica NA320



Leica NA324



Leica NA332

TECHNICAL DATA

Standard deviation for 1 km double levelling (ISO17123-2)	2.5 mm	2.0 mm	1.8 mm
---	--------	--------	--------

TELESCOPE

Telescope image	Upright		
Magnification	20 x	24 x	32 x
Objective aperture	36 mm		
Shortest target distance from instr. axis	< 1.0 m		
Field of view at 100 m	< 2.1 m		
Multiplication factor	100		
Additive constant	0		

COMPENSATOR

Working range	± 15'
Setting accuracy (standard deviation)	< 0.5"
Sensitivity	8'/2 mm

HORIZONTAL CIRCLE

Graduation	360°
Graduation interval	1°
Weight (net)	1.5 kg
Operating temperature range	-20° C to +40° C



PROTECT is subject to Leica Geosystems' international manufacturer warranty and the general terms and conditions for PROTECT. For more information visit www.leica-geosystems.com/protect

Leica Geosystems offers a wide variety of construction instruments for your everyday use. Contact your local Leica Geosystems dealer for more information on our solutions.



Pipe Lasers

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland - Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2016. 843989en - 01.16 - INT

- when it has to be **right**

Leica
Geosystems