Sport Runabout 14sr Standard Features

- · NMMA & CE Certified
- · Smooth rounded hull shape for less drag and more efficient motoring
- · Wide beam hull design for stability and added capacity
- Patented (U.S. Patent #8,286,573 2) outside Drop-Stitch inflatable keel for smoother ride, super precise steering and faster planing
- Choice of 6" Drop-Stitch (DS) floor for easiest assembly and lightest weight or rugged polyethylene floorboards

Our Boat With The Most!

Ever since using the original Sea Eagle 14sr to run around Long Island, we have been impressed with the seaworthiness and the rugged capabilities of this great size. Now that it features a wider bow with a smoother curved shape and even more flotation, we can tell you this new improved model rides even better through waves and rough seas.

Want to go offshore 15 miles, the 14sr can do it. Want to go through inlets with 8 to 10 mile currents, the 14sr can do it. Want to carry people, gas and supplies to take you a 100 miles, the 14sr can do it.

This is our largest, our most rugged, our most seaworthy transom boat. The Sea Eagle 14sr is the Queen of the Line.



Deluxe Package • 14sr Hull with Boat Bag • 6" High Pressure Inflatable

- Drop-Stitch Floor Or Polyethylene Plastic Floorboard Set
- One Aluminum
- Bench Seat

 One AB255 Collapsible Oar Set

Wide Canopy

One Bow BagOne Auto Dual Action Piston Pump (w/Drop-Stitch Floor) Or Foot Pump with Polyethylene Floor



 Hefty %" grab line running through brass grommets & a line of double layer fabric hogging on sides for

- Rounded rear pontoons for rapid planing
- · Splash guards on transom
- · Two stainless steel D-Rings for easy towing
- Four side carry handles & front lifting handle
- · Oarlocks pop up for instant use

- · Rubbing strake around hull and under Keel for extra
- · Two layers of material on lower tubes for greatest abrasion and puncture resistance
- Easy open or shut self bailing Bravo drain valve located inside of boat for easy access
- Nylon carry bag
- · Repair kit & printed instructions

