THE FIREWALL FR®

Browse through our Firewall Wear Catalog. The Items that are on our website are the items we stock. However we can special order most of the items in this catalog.Some limitations may apply To get Current Pricing and Availability Call 1-800-561-3600 or email info@bapequipment.com

Viking® Firewall FR® is committed to providing industry leading Flame Resistant garments that offer the highest level of safety for workers exposed to electrical arc an hydrocarbon flash fire hazards.



Viking[®] Firewall FR[®] has partnered with Westex[®] by Milliken[®] to supply best-in-class inherent and treated flame-resistant fabrics for Viking Firewall FR[®] FR garment. Milliken & Company, with the recent acquisition of Westex[®], is the largest flame resistant fabric manufacturer in the world and a market leader in innovation and technology.

Fabric Choices for All Industry Applications

Viking® Firewall FR® garments are offered in inherent or treated flameresistant fabrics by Westex® by Milliken.®. Westex® by Milliken® treated FR fabric® is made of 88% cotton, 12% nylon blend with a proprietary permanent FR treatment process guaranteed for the life of the garment. Westex® CXP® flame-resistant fabric, made of Nomex® IIIA fibres, offers greater comfort and durability than other Nomex® IIIA fabrics. Nomex® CXP® combines the Softouch Technology™ process with Leap® technology to provide a soft Nomex® fabric that protects against both arc flash and flash fire hazards.

Westex[®] by Milliken[®] Flame Resistant Fabrics

Westex® by Milliken® 88% cotton / 12% Nylon are high performance flame-resistant (FR) fabrics specifically "Wellew designed for industrial workwear. The proprietary fabrics use a specialized ammonia-free FR treatment process and are constructed of an optimized blend of Pima cotton and high-tenacity Nylon designed to help mitigate potential injuries due to electric arc and flash fire exposure, while providing enhanced durability and comfort. The combination of these capabilities makes it an ideal fabric for industrial workwear occupations in manufacturing, utilities, electrical maintenance, petrochemical, welding, and steel.

Westex® by Milliken®'s excellent protection against Flash Fire and Arc Flash can significantly reduce the risk of burns. With high air permeability, fabrics breathe, keeping the wearer more comfortable.

Westex[®] by Milliken[®] fabric is UL Certified to NFPA 2112, CAN/CGSB-155.20, NFPA 1975 (7 oz only), NFPA 1977 and Arc Rated according to ASTM F1506 for NFPA 70E as HRC/CAT 2.

Westex[®] CXP[®] Nomex[®] Flame Resistant Fabric

Westex[®] CXP[®] is a patented, flame-resistant fabric made of DuPont[™] Nomex[®] IIIA. The fabric is more comfortable and lasts longer than comparable Nomex[®] fabrics, and is the best choice for protective industrial uniforms and for fire service.



Milliken®'s Softouch Technology® ensures that Westex® CXP® is soft to the touch and has improved airflow through the fabric and the proprietary Visa® technology provides superior wicking for moisture management and helps oily stains wash out. Plus, Westex® CXP® is 40% lighter than FR Cotton/Nylon 9 oz. fabrics, an important factor in overall comfort. All of this keeps you cool and dry while working in hot environments.

Westex* CXP* fabric is UL Certified to NFPA 2112, CAN/CGSB-155.20 (155.22), NFPA 1975, NFPA 1977 and Arc Rated according to ASTM F1506 for NFPA 70E as HRC/CAT 1.

Milliken[®] DuPont[™] Nomex[®] CXP[®] HRC 2 Inherent Flame Resistant Fabric

Nomex® CXP® fabric by Milliken® was specifically developed to provide

improved comfort with dual-hazard fire and electric arc protection. This uniquely made fabric also offers the proven durability, life cycle value and inherent flame resistance that you have come to expect from Nomex[®].

Nomex[®] CXP[®] is a patented, inherently flame-resistant fabric innovation that helps protect against both fire and electric arc flash hazards. This dual-hazard solution combines proprietary technology engineered by Milliken[®] to enhance arc protection for DuPont[™] Nomex[®]—which is recognized as a leading flame-resistant (FR) fabric for fire protection in oil and gas, military, emergency response and automobile racing applications. Nomex[®] CXP[®] is UL Certified to NFPA 2112, CAN/CGSB-155.20 (155.22), NFPA 1975, NFPA 1977 and Arc Rated according to ASTM F1506 for NFPA 70E as HRC/CAT2.

Viking[®] Firewall FR[®] products offer superior safety performance, improved comfort and durability, and best value in FR safety workwear



Viking[®] Firewall FR[®] Button Front Shirt

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 7 oz. Westex[®] by Milliken[®] flame-resistant fabric 88% cotton/ 12% nylon
 TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2 (HRC 2)
- Button front closure with full-length placket with a button-down collar
- Full sleeves with adjustable button cuffs
- 2 chest pockets with button closure and box pleat on back
- Dual hazard protection from electrical arc and hydrocarbon flash fire



Size SR - 4XLT



WESTEX

milliken,



Viking[®] Firewall FR[®] Cargo Pants

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- + 9 oz. Westex* by Milliken* flame-resistant fabric 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2 (HRC 2)
- All brass closures thermally protected from the skin
- · Dual hazard protection from electrical arc and hydrocarbon flash fire
- Cargo style work pants
- Reinforced front slant pockets and back seat pockets
- · Generous sized side pockets with flaps, and hook-and-loop closure
- Belt loops, metal button waist closure and $\mathsf{Nomex}^{\texttt{B}}$ backed $\mathsf{YKK}^{\texttt{B}}\mathsf{zipper}\,\mathsf{fly}$

Browse through our Firewall Wear Catalog. The Items that are on our website are the items we stock. However we can special order most of the items in this catalog. Some limitations may apply

To get Current Pricing and Availability Call 1-800-561-3600 or email <u>info@bapequipment.com</u>





Size 30 - 48

For Current Pricing and Availability Call 1-800-561-3600 or email info@bapequipment.com



Viking[®] Firewall FR[®] Striped Coveralls

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- "Oil Patch" style reflective striping configuration
- RT80 featuring 3M Scotchlite™ Reflective Material 9740 industrial wash flame resistant trim (2" yellow/silver/yellow) with X on back and stripes around each forearm and each leg below the knee
- Two-way breakaway Nomex[®] backed YKK[®] front zipper
- · Adjustable cuffs, tunnel collar with hook-and-loop closure
- 2 front upper pockets (including 1 mesh gas monitor pocket), and 2 lower front pouch pockets with side access vents
- 1 tool pocket on rear right leg, and 1 left sleeve pencil pocket
- Elasticized waist on the back and fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- · Dual hazard protection from electrical arc and hydrocarbon flash fire

405791200 available in XSR - 5XLT



40577 Viking[®] Firewall FR[®] Striped Coveralls 7 oz.

- 7 oz. Westex by Milliken® flame-resistant fabric 88% cotton / 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2 (HRC 2)

40579 Viking[®] Firewall FR[®] Striped Coveralls 9 oz.

- 9 oz. Westex by Milliken® flame-resistant fabric 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2 (HRC 2)

Viking[®] Firewall FR[®] CSA High Visibility FR Coveralls

- Fully compliant with CSA Z96-15 Class 3, level 2
- Meets WCB/Worksafe BC/DOT configuration
- RT80 featuring 3M Scotchlite™ Reflective Material–9740 industrial wash flame-resistant trim (4" yellow/silver/yellow)
- Two-way breakaway Nomex[®] backed YKK[®] front zipper, adjustable cuffs, tunnel collar with hook-and-loop closure
- 2 front upper pockets (including 1 mesh gas monitor pocket), and 2 lower front pouch pockets with side access vents
- 2 chest straps
- 1 tool pocket on rear right leg, and 1 left sleeve pencil pocket
- Elasticized waist on the back and fully stitched bi-swing back for better fit and mobility
- · All seams double-stitched and stress points bar tacked for ultimate durability
- · Dual hazard protection from electrical arc and hydrocarbon flash fire

40479 available in SR - 5XLT Size SR - 4XLR

3M Scotchlite" & WESTEX"

40477 Viking[®] Firewall FR[®] CSA High Visibility FR Coveralls 7 oz.

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 7 oz. Westex by Milliken® flame-resistant fabric 88% cotton / 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2

40479 Viking $^{\rm \tiny B}$ Firewall FR $^{\rm \tiny B}$ CSA High Visibility FR Coveralls 9 oz.

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- + 9 oz. Westex by Milliken® flame-resistant fabric 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2 (HRC 2)

<image>

40479

5400 Orange

1200 Royal Blue

100 Dark Navy

200 Roval Blue

Viking[®] Firewall FR[®] CSA Striped Coveralls

- RT80 featuring 3M Scotchlite[™] Reflective Material 9740 industrial wash flame resistant trim (2" yellow/silver/yellow). CSA Z96-15 Class 1, Level FR striping pattern.
- Two-way breakaway Nomex® backed YKK® front zipper
- · Adjustable cuffs, tunnel collar with hook-and-loop closure
- 2 front upper pockets (including 1 mesh gas monitor pocket), and 2 lower front pouch pockets with side access vents
- 2 chest straps
- One tool pocket on rear right leg, one left sleeve pencil pocket
- Elasticized waist on the back and fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire

1100 and 1200 available in XSR - 5XLR; 5400 available in SR - 4XLR

Size SR - 5XLR



40677 Viking[®] Firewall FR[®] CSA Striped Coveralls 7 oz.

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 1, Level FR.
- High visibility orange (5400) complies with CSA Z96-15 Class 3, Level FR
- 7 oz. Westex® by Milliken® flame-resistant fabric 88% cotton / 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2 (HRC 2)

40679 Viking[®] Firewall FR[®] CSA Striped Coveralls 9 oz.

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 3, Level FR
- 9 oz. Westex® by Milliken® flame-resistant fabric 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2 (HRC 2)

Viking[®] Firewall FR[®] Miner 49er Mining Coveralls

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 3, Level 2
- 2" Vi-brance® flame-resistant industrial wash reflective tape
- 7 oz. Westex® by Milliken® flame-resistant fabric 88% cotton / 12% nylon
- TPP Value: Contact 8.5, Spaced 9.0
- ARC rating ATPV: 9.2 cal/cm² CAT 2 (HRC 2)
- Two-way breakaway Nomex® backed YKK® front zipper
- Adjustable cuffs, tunnel collar with snap closure
- 2 front upper pockets, and 2 lower front pouch pockets
- · Fully stitched bi-swing back for better fit and mobility
- All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire

Browse through our Firewall Wear Catalog. The Items that are on our website are the items we stock. However we can special order most of the items in this catalog. Some limitations may apply

To get Current Pricing and Availability Call 1-800-561-3600 or email <u>info@bapequipment.com</u>

. WESTE

Willih











Viking[®] Firewall FR[®] CXP[®] Nomex[®] CSA Striped Coveralls

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 (Class 1/Level FR)
- 5.8 oz. DuPont[®] CXP[®] HRC2 Nomex[®] IIIA
- TPP Value: Contact 7.9, Spaced 13.5
- ARC rating ATPV: 10.2 cal/cm² CAT 2 (HRC 2)
- RT80 featuring 3M Scotchlite[™] Reflective Material–9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex[®] backed YKK[®] front zipper
- · Adjustable cuffs, tunnel collar with hook-and-loop closure
- 2 front upper pockets (including 1 mesh gas monitor pocket), and 2 lower front pouch pockets with side access vents
- 1 tool pocket on rear right leg, and 1 left sleeve pencil pocket
- · Elasticized waist on the back and fully stitched bi-swing back for better fit and mobility
- · All seams double-stitched and stress points bar tacked for ultimate durability
- Dual hazard protection from electrical arc and hydrocarbon flash fire

Browse through our Firewall Wear Catalog. The Items that are on our website are the items we stock. However we can special order most of the items in this catalog. Some limitations may apply

To get Current Pricing and Availability Call 1-800-561-3600 or email info@bapequipment.com

40665

1200 Royal Blue

Size SR - 3XLT



Viking[®] Firewall FR[®] CXP[®] Nomex[®] IIIA CSA Striped Bib **Overalls**

- Meets safety standards: PPE Category 1, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 (Class 1/Level FR)
- 5.8 oz. DuPont® CXP® HRC2 Nomex® IIIA
- TPP Value: Contact 7.9, Spaced 13.5
- ARC rating ATPV: 10.2 cal/cm² CAT 2 (HRC 2)
- RT80 featuring 3M Scotchlite[™] Reflective Material 9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex® backed YKK® front zipper with exterior storm flap closure
- · Shoulder suspenders with adjustable buckles
- 2 front upper chest pockets, 2 large back pockets, and 2 lower front patch pockets
- · Right tool pocket and hammer loop on left rear
- · All seams double-stitched and stress points bar tacked for ultimate durability
- · Dual hazard protection from electrical arc and hydrocarbon flash fire



Size S - 5XL

Viking[®] Firewall FR[®] CSA Striped Bib Overalls

- Meets safety standards: PPE Category 2, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 1, Level FR
- High visibility orange (5400) complies with CSA Z96-15 Class 2, Level FR
- 9 oz. Westex® by Milliken® flame-resistant fabric 88% cotton / 12% nylon
- TPP Value: Contact 10.3, Spaced 11.4 ARC rating ATPV: 12.4 cal/cm² CAT 2 (JRC 3)
- RT80 featuring 3M Scotchlite™ Reflective Material 9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex[®] backed YKK[®] front zipper with exterior storm flap closure
- · Shoulder suspenders with adjustable buckles
- 2 front upper chest pockets, 2 large back pockets, and 2 lower front patch pockets
- · Right tool pocket and hammer loop on left rear
- · All seams double-stitched and stress points bar tacked for ultimate durability
- · Dual hazard protection from electrical arc and hydrocarbon flash fire

Browse through our Firewall Wear Catalog. The Items that are on our website are the items we stock. However we can special order most of the items in this catalog. Some limitations may apply

To get Current Pricing and Availability Call 1-800-561-3600 or email info@bapequipment.com

```
3M Scotchlite<sup>*</sup>
Size S - 5XI
```

Viking[®] Firewall FR[®] CXP[®] Nomex[®] Striped Insulated **Overalls**

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 5.8 oz. DuPont[®] CXP[®] HRC2 Nomex[®] IIIA (outer shell)
- · 12 oz. quilted modacrylic lining with wind and vapor barrier
- TPP Value: Contact 7.9, Spaced 13.5
- ARC rating ATPV: 32 cal/cm² CAT 3 (HRC 3)
- RT80 featuring 3M Scotchlite[™] Reflective Material–9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)-striping around lower legs
- Easy boot access with 15.5" Nomex[®] backed YKK[®] leg zippers
- · Elastic shoulder suspenders with adjustable buckles
- 1 upper pocket with closure and pencil slot, 2 rear patch pockets, 2 lower front patch pockets, 1 right tool pocket
- · Double knees and elastic waistband
- · Dual hazard protection from electrical arc and hydrocarbon flash fire



41679

1100 Dark Navy 200 Royal Blue 400 Orange



51566 1200 Royal Blue



• WESTEX

Willie.



Viking[®] Firewall FR[®] Striped Insulated Overalls

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- + 9 oz. Westex $^{\otimes}$ by Milliken $^{\otimes}$ flame-resistant fabric 88% cotton / 12% nylon (outer shell)
- 12 oz. quilted modacrylic lining with wind and vapor barrier
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 35 cal/cm² CAT 3 (HRC 3)
- RT80 featuring 3M Scotchlite™ Reflective Material 9740 industrial wash flame resistant trim (2" yellow/silver/yellow) – Striping around Lower Legs.
- Nomex[®] backed YKK[®] two-way breakaway front zipper with exterior storm flap closure
- Easy boot access with 15.5" Nomex[®] backed YKK[®] leg zippers
- Elastic shoulder suspenders with adjustable buckles
- 1 upper pocket with closure and pencil slot, 2 rear patch pockets, 2 lower front patch pockets, 1 right tool pocket
- · Double knees and elastic waistband
- Dual hazard protection from electrical arc and hydrocarbon flash fire



Viking[®] Firewall FR[®] Striped Insulated Overalls

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269, CSA Z96-15 Class 2/Level FR
- 9 oz. Westex[®] by Milliken[®] flame-resistant fabric 88% cotton / 12% nylon (outer shell)
- · 12 oz. quilted modacrylic lining with wind and vapor barrier
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 35 cal/cm² CAT 3 (HRC 3)
- Nomex[®] backed YKK[®] Two-way breakaway front zipper with exterior storm flap closure
- Easy boot access with 15.5" Nomex® backed YKK® leg zippers
- Elastic shoulder suspenders with adjustable buckles
- 2 rear patch pockets, 2 lower front patch pockets, 1 right tool pocket
- · Double knees and elastic waistband
- Dual hazard protection from electrical arc and hydrocarbon flash fire

Browse through our Firewall Wear Catalog. The Items that are on our website are the items we stock. However we can special order most of the items in this catalog. Some limitations may apply

To get Current Pricing and Availability Call 1-800-561-3600 or email <u>info@bapequipment.com</u>



5400 Orange

100 Dark Navy

200 Royal Blue

Size M - 4XL



Viking[®] Firewall FR[®] CSA Striped Insulated Parka

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70-2015, OSHA 1910.269, CSA Z96-15 Class 1/Level FR
- High visibility orange (5400) is compliant with CSA Z96-15 Class 2/Level FR
- 9 oz. Westex[®] by Milliken[®] flame-resistant fabric 88% cotton / 12% nylon (outer shell)
- · 12 oz. Quilted modacrylic lining with wind and vapour barrier
- TPP Value: Contact 10.3, Spaced 11.4
- ARC rating ATPV: 35 cal/cm² CAT 3 (HRC3)
- RT80 featuring 3M Scotchlite™ Reflective Material 9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex* backed YKK^{\otimes} front zipper with exterior storm flap closure
- Tunnel collar with closure
- 2 large upper chest pockets (including 1 mesh gas monitor pocket), 2 oversized lower front patch pockets with closure flaps and side entry hand warmer pockets with FR fleece pocket lining
- Left sleeve pencil pocket and 1 left inside pocket
- 2 chest straps
- · Bi-swing back with elasticized waistband and drawstring with cord locks
- · FR storm cuffs
- Snap-on hard hat hood sold separately (68G79)
- Dual hazard protection from electrical arc and hydrocarbon flash fire



55679

L100 Dark Navy

5400 available in SR - 4XLR		
Size XSR - 5XLT	3M Scotchlite ^{**}	by Milliken

Viking[®] Firewall FR[®] CXP[®] Nomex[®] Striped Insulated Parka

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 5.8 oz. DuPont[®] CXP[®] HRC2 Nomex[®] IIIA (outer shell)
- 12 oz. Quilted modacrylic lining with wind and vapour barrier
- TPP Value: Contact 7.9, Spaced 13.5
- ARC rating ATPV: 32 cal/cm² CAT 3 (HRC 3)
- RT80 featuring 3M Scotchlite™ Reflective Material 9740 industrial wash flame-resistant trim (2" yellow/silver/yellow)
- Two-way breakaway Nomex* backed YKK^{\otimes} front zipper with exterior storm flap closure
- Tunnel collar with closure
- 2 large upper pockets (including 1 mesh gas monitor pocket), 2 lower front patch pockets with closure flaps and side entry
- Left sleeve pencil pocket, and 1 left inside pocket
- 2 chest straps
- · Bi-swing back with elasticized waistband and drawstring with cord locks
- · FR storm cuffs, thread, and tape
- Dual hazard protection from electrical arc and hydrocarbon flash fire

Browse through our Firewall Wear Catalog. The Items that are on our website are the items we stock. However we can special order most of the items in this catalog. Some limitations may apply

To get Current Pricing and Availability Call 1-800-561-3600 or email <u>info@bapequipment.com</u>





1200 Royal Blue



Viking[®] Firewall FR[®] Hard Hat Winter Hood

- Meets safety standards: PPE Category 3, CAN/CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 9 oz. Westex[®] by Milliken[®] Flame Resistant Fabric 88% cotton/12% nylon (outer shell)
- 12 oz. Quilted modacrylic lining with wind and vapour barrier
- TPP Value: Contact: 10.3, Spaced 11.4
- ARC rating ATPV: 35cal/cm²
- CAT 3 (HRC 3)

Size Fits all

- Front drawstring closure with cord locks
- FR hook-and-loop closing storm flap face protector
- Snap onto Style 55679 parka, and 55566 insulated parka



62F00



6T779 1200 Royal Blue



Nomex[®] IIIA Knit Toque

- Meets safety standards: CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- Nomex[®] IIIA knit fabric
- Double thick knit construction
- Flat seaming for comfort

Browse through our Firewall Wear Catalog. The Items that are on our website are the items we stock. However we can special order most of the items in this catalog. Some limitations may apply

To get Current Pricing and Availability Call 1-800-561-3600 or email info@bapequipment.com

Size Fits all



Viking[®] Firewall FR[®] Ankle Guard

- Meets safety standards: PPE Category 2, CGSB 155.20-2000, CSA Z462-15, ASTM F1506, NFPA 70E-2015, OSHA 1910.269
- 9 oz. Westex* by Milliken* Flame Resistant Fabric 88% cotton/12% nylon blend
- TPP Value: Contact: 10.3, Spaced 11.4
- ARC rating ATPV: 12.4 cal/cm² CAT 2
- · 2 layers of fabric
- · Hook and loop closure

