





**Tapered** 

X-Emboss

**High Attenuation** 

Soft PU foam

protective equipment

Compatible with other personal

Disposable Earplugs "Dyna-Fit"

MEETS ANSI S3.19-1974 REGULATION & CANADIAN CLASS A(L) STANDARDS

- Excellent protection Very high absorption level
- Excellent sound Top voice recognition
- Excellent fit Very comfortable to wear
- The ergonomically shaped Dynamic "Dyna-fit"

Disposable earplugs are characterized by very high sound absorption levels, making it suitable for use in very loud environments. The "Dyna-Fit" foam earplug has a sealed surface, preventing foreign bodies from penetrating the plug. The soft foam offers real comfort, even when worn for extended periods.

The "X" embossed in the end of the plug makes it easy to remove while simultaneously reducing the pressure on the outer wall of the ear canal.

Model:	NP101
Color:	Red - Cordless
Packaging:	1 pair per bag
	200 bags per dispenser box
	10 dispenser boxes per case
Model:	NP101C
Color:	Red – with cord
Packaging:	1 pair per bag
	100 bags per dispenser box

10 dispenser boxes

per case

SNR: 37 dB			H: 3	6 dB	M: 3	84 dB	L: 3	4 dB
Frequency Hz	63	125	250	500	1000	2000	4000	8000
Mean Attenuation dB	35.3	38.4	39.3	40.8	38.9	37.8	45.9	45.1
Standard Deviation dB	4.2	6.3	5.3	5.5	5.5	4.3	3.9	4.6
Assumed Protection dB (APV)	31.1	32.1	34.0	35.3	33.4	33.5	42.0	40.5

NRR: 32 dB		CSA Class A(L) Standards / ANSI S3.19-1974 Regulations									
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation dB	39.9	41.8	42.3	38.2	35.6	42.1	43.9	46.8	47.1		
Standard Deviation dB	4.2	4.4	3.7	2.4	2.2	2.3	2.8	4.1	3.2		
Assumed Protection dB (APV)	31.5	33.0	34.9	33.4	31.2	37.5	38.3	38.6	40.7		

N	Р1	01

#### FEATURES ADVANTAGES

Fits to the natural contour of the ear canal

Less materiel at the entrance to the ear canal

High and immediate noise reduction

Allows the user to wear all necessary protection & equipment needed in a work situation

Slow expansion to perfectly fit the size and form of the ear canal

Light & comfortable with a secure fit, Give optimum performance and protection

Reduce expansion pressure for optimal comfort and all day use

Minimizes disturbance and unpleasant noise levels

Improved conformity to safety requirements


**BENEFITS** 

Increase hygiene, Maximum performance, long wearing comfort


Ideal for use in workshops, manufacturing, construction and other work environments.

# Disposable Earplugs "Dyna-Fit Lite"

MEETS ANSI S3.19-1974 REGULATION & CANADIAN CLASS A(L) STANDARDS



Model:	NP102
Color:	Orange - Cordless
Packaging:	1 pair per bag
	200 bags per dispenser box
	10 dispenser boxes per case
Medel	ND1000
Model:	NP102C
Color:	Lime-Green - with cord
Packaging:	1 pair per bag
	100 bags per dispenser box
	10 dispenser boxes



NRR: 30 dB			C	SA Class A	(L) Standa	rds / ANSI	S3.19-197	'4 Regulati	ons
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000
Mean Attenuation dB	31.5	30.2	35.6	35.1	38.4	42.8	45.5	47.4	46.6
Standard Deviation dB	3.9	2.9	2.9	2.9	2.6	3.6	4.6	2.7	3.1
Assumed Protection dB (APV)	23.7	24.4	29.8	29.3	33.2	35.6	36.3	42	40.4

# The highly innovative "Dyna-Fit Lite" disportically reduces the level be built up in the inner hearing protectors. The and cavity design income and absorption. The acoustics and absorption. The acoustics and absorption. The acoustics and absorption. The acoustics and absorption making it possible to warning sounds clear superb comfort, even The inner cavity mak since it reducing the wall of the ear canal. SNR: 36 dB Frequency Hz Mean Attenuation dB Assumed Protection dB in the NRR: 30 dB Frequency Hz NP102C

**FEATURES** 

Unique Design

Hollow Middle

Larger Surface Area

#### **ADVANTAGES**

Minimal pressure in the ear canal Absorbs inner ear sound

Designed to fit the natural form of the ear canal

Low and direct noise attenuation

#### **BENEFITS**

Superb comfort

Smallest possible diameter for easier insertion

Expansion pressure adjusted for optimal comfort

optimal comfort

Simple insertion and hygienic removal after use

Reduced attenuation gives improved voice comprehension and awareness of warning signals

Ideal for use in manufacturing, warehouses and distribution, building and construction, energy, oil & gas





# Disposable & Detectable Earplugs "Dyna-Fit Detect"

MEETS ANSI S3.19-1974 REGULATION & CANADIAN CLASS A(L) STANDARDS

The DYNAMIC "DYNA-FIT DETECT" NP101CD is a copy of the "DYNA-FIT" NP101C to the exception that it is detectable due to the addition of a metal insert connected to the cord. This product was made for the food industry and for that reason it's color is of a bright blue which make it easier to trace if by accident it falls into food production areas.

The DYNAMIC "DYNA-FIT DETECT" is safe, comfortable with a high NRR rating easily detectable due to it s metal insert and it's bright blue color plus it is very economical. The blue connecting PVC cord makes this product practical to wear and limits the risk of process contamination.

Model:	NP101CD
Color:	Bright Blue - with cord
Packaging:	1 pair per bag
	100 bags per dispenser box
	10 dispensers boxes per case

SNR: 37 dB				H: 36 dB		M: 34 dB		L: 34 dB	
Frequency Hz	63	125	250	500	1000	2000	4000	8000	
Mean Attenuation dB	35.3	38.4	39.3	40.8	38.9	37.8	45.9	45.1	
Standard Deviation dB	4.2	6.3	5.3	5.5	5.5	4.3	3.9	4.6	
Assumed Protection dB (APV)	31.1	32.1	34.0	35.3	33.4	33.5	42.0	40.5	

NRR: 32 dB			CSA Class A(L) Standards / ANSI S3.19-1974 Regulations							
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000	
Mean Attenuation dB	39.9	41.8	42.3	38.2	35.6	42.1	43.9	46.8	47.1	
Standard Deviation dB	4.2	4.4	3.7	2.4	2.2	2.3	2.8	4.1	3.2	
Assumed Protection dB (APV)	31.5	33.0	34.9	33.4	31.2	37.5	38.3	38.6	40.7	

ľ	H	E	A	I	U	ŀ	1	E	S
ı	n	ο.	te	۱۵	٠+	2	ıh	١I	6

Detectable foam plug

X-Emboss

**High Attenuation** 

Compatible with other personal protective equipement

Traceable Cord

#### **ADVANTAGES**

Fits to the natural contour of the ear canal Easily tracable by a metal detector

Less bulky material at the entrance to the ear canal

High and immediate noise reduction Slow expansion to perfectly fit the size and form of the ear canal

Allows the user to wear all necessary protective equipment needed to work safely

Increase safety and protect production

#### **BENEFITS**

Light and comfortable with a secure fit Provides optimal performance and protection

Reduces expansion pressure for optimal comfort and all day use Simple insertion and hygienic removal after use

Minimizes disturbance and unpleasant noise level

Improved conformity

Contains metal material making it easy to trace





## Reusable Earplugs "Quiet-Fit"

#### MEETS ANSI S3.19-1974 REGULATION & CANADIAN CLASS A(L) STANDARDS

This multiple flange ultra soft TPE reusable plug is the right answer for dirty, not too noisy work environments. (Up to a noise level of less than 100dB). The smooth, dirt- repellant surface of the DYNAMIC "QUIET-FIT" Reusable earplug will prevent the plug from collecting irritating particles that can cause injuries to the ear canal. The plug can be easily cleaned using soap and water in order to maintain excellent wearer comfort and safety.

The corded "QUIET-FIT" provided with a string material made cord that does not transfer the sound even on your neck or clothing. When not in use the plugs can be stored into the original packaging of a small ziplock type bag.

NP103							
Red - Cordless							
1 pair per bag							
100 bags per dispenser box							
10 dispensers boxes per case							
NP103C							
Red – with cord							
1 pair per bag							
100 bags per							

dispenser box

per case

10 dispenser boxes

SNR: 23 dB			H: 24 dB		M: 20 dB		L: 17 dB	
Frequency Hz	63	125	250	500	1000	2000	4000	8000
Mean Attenuation dB	23.7	23.2	21.1	22.6	24.8	31.7	33.4	39.4
Standard Deviation dB	5.6	5.8	6.8	5.2	5.7	6.0	9.5	8.2
Assumed Protection dB (APV)	18.1	17.4	14.3	17.4	19.1	25.7	23.9	31.2

NRR: 23 dB			C	SA Class A	(L) Standa	rds / ANSI	S3.19-197	'4 Regulati	ons
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000
Mean Attenuation dB	31.6	31.1	32.9	30.8	33.7	38.0	38.2	42.7	45.6
Standard Deviation dB	4.2	3.9	4.3	4.1	4.5	4.5	3.7	4.4	4.9
Assumed Protection dB (APV)	23.2	23.3	24.3	22.6	24.7	29	30.8	33.9	35.8

# **NP103** NP103C

#### **FEATURES**

Reusable Ultra-soft TPE plug

Pre-Formed stem with no rolling

Moderate attenuation

Removable Cord

Packaged in small Zip-Lock type bag.

#### **ADVANTAGES**

Self sealing flanges

Can be used in noise level up 100dB(A)

Simple insertion without having to roll the plug prior to insertion.

Soft and comfortable feel on contact with the skin.

Excellent for speech clarity and comprehension.

Multiple Choices

When working with machines the cord could be detached easily for added safety.

Easy to store in the Zip-Lock bag when not in use.

#### **BENEFITS**

Provide all day comfort Can be reused several times

Reduce the risk for unhygienic contamination

Safe usage that blocks out hazardous noise yet allows warning signals and voice to be clearly understood.

Safe and secure

The earplugs can be removed and cleaned with mild soap and water

Reusable which make these plugs very cost effective

Ideal for use in workshops, warehouses, light manufacturing and other area where noise is under 100dB(A).

# Reusable Earplugs "Comfort-Fit"

MEETS ANSI S3.19-1974 REGULATION & CANADIAN CLASS A(L) STANDARDS

This DYNAMIC 4 multi flange reusable plug is by far the softest TPE plug offered in the market today, it provides a high attenuation ratio of NRR 25dB. The smooth dirt-repellant surface of the plug will prevent the plug from collecting irritating particles that can cause injuries to the ear canal. Easy to clean with mild soap and water maintaining ultimate comfort to the

The corded "COMFORT-FIT" plug is provided with a string material cord that does not transfer sound even when rubbing against your neck or clothing. The cord can be removed if need be.

When not in use the plug store's into the reusable packet it came in.

Model:	NP104			
Color:	Orange - Cordless			
Packaging:	1 pair per reusable pack			
	100 pair per inner box			
	10 inner boxes per case			

Model:	NP104C			
Color:	Orange - with cord			
Packaging:	ing: 1 pair per reusable pack			
	100 pair per inner box			
	10 inner boxes			
	per case			

SNR: 27 dB			H: 24 dB		M: 22 dB		L: 27 dB	
Frequency Hz	63	125	250	500	1000	2000	4000	8000
Mean Attenuation dB	26.6	26.9	24.3	26.1	28.8	32.8	32.6	38.1
Standard Deviation dB	6.1	6.1	4.1	5.1	5.1	5	6.5	5.3
Assumed Protection dB (APV)	20.5	20.8	20.2	21.0	23.7	27.8	26.1	32.8

NRR: 27 dB			CS	SA Class A	(L) Standa	rds / ANSI	S3.19-197	'4 Regulati	ons
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000
Mean Attenuation dB	34.3	31.2	35.3	32.9	39.0	38.6	38.3	40.1	42.5
Standard Deviation dB	5.2	4.1	3.4	3.4	3.6	3.1	3.6	4.3	3.0
Assumed Protection dB (APV)	23.9	23.0	28.5	26.1	31.8	32.4	31.1	31.5	36.5

#### **FEATURES**

NP104C

Multiple-Flange TPE earplug.

Pre-Formed stem with no rolling required

NP104

Even and Moderate Attenuation

Removable Cord

Comes in small packets.

#### **ADVANTAGES**

Self-sealing flange

Seals against hazardous noise ,water and others unusable particles.

Stiffened shaft makes insertion easy and avoids contact with the parts inserted into the ear.

Soft and comfortable feel on contact with the skin.

Excellent for speech clarity and comprehension.

Multiple Choice

Natural sound

When working with machines the cord can be detached easily for added safety.

Easy to store in the packet when not in use.

#### RENEFITS

Provides all day comfort Can be reused several times

Reduces the risk of unhygienic contamination.

Simple insertion and hygienic removal after use Safe usage that blocks out hazardous noise yet allows warning signals and voices to be clearly understood.

Safe and secure

The earplug can be removed and cleaned with mild soap and water Reusable, which makes the product more economical

Ideal for use in light manufacturing areas, dairies, laboratories, canning, pharmaceuticals and many others.





# Reusable & Detectable Earplugs "Comfort-Fit Detect"

MEETS ANSI S3.19-1974 REGULATION & CANADIAN CLASS A(L) STANDARDS

Highly comfortable, Noise absorbent, Reusable, Detectable and safe - The new "COMFORT-FIT DETECT" is all of these. These reusable earplugs are made of washable plastic from MEDICAL Industry technology. This product is also made for the food industry. Its bright blue colour makes it easier to detect in production areas and it is reusable, making it more economical.

Model:	NP104CD
Color:	Bright Blue - with cord
Packaging:	1 pair per small reusable box
	100 pair per inner box
	10 inner boxes
	per case

SNR: 27 dB			H: 2	.4 dB	M: 2	22 dB	L: 2	?7 dB
Frequency Hz	63	125	250	500	1000	2000	4000	8000
Mean Attenuation dB	26.6	26.9	24.3	26.1	28.8	32.8	32.6	38.1
Standard Deviation dB	6.1	6.1	4.1	5.1	5.1	5	6.5	5.3
Assumed Protection dB (APV)	20.5	20.8	20.2	21.0	23.7	27.8	26.1	32.8

NRR: 27 dB			C	SA Class A	(L) Standaı	rds / ANSI	S3.19-197	'4 Regulati	ons
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000
Mean Attenuation dB	34.3	31.2	35.3	32.9	39.0	38.6	38.3	40.1	42.5
Standard Deviation dB	5.2	4.1	3.4	3.4	3.6	3.1	3.6	4.3	3.0
Assumed Protection dB (APV)	23.9	23.0	28.5	26.1	31.8	32.4	31.1	31.5	36.5

#### **FEATURES**

Detectable Reusable earplug.

Pre-Formed stem with no rolling

Moderate attenuation

Traceble Cord

Package in small reusable case

#### **ADVANTAGES**

Easy to trace with a metal detector. Self-sealing flanges.

Stiffened shaft makes insertion easy and avoids contact with the parts inserted into the ear canal.

Soft and comfortable feel on contact.

Natural sound

Excellent voice clarity and speech comprehension.

Increases safety and convenience

Easy to store in the pocket when not in use.

#### **BENEFITS**

Comfortable even when used for long periods

Reduces the risk for making it dirty. Simple insertion and hygienic removal after use.

Safe usage that blocks out hazardous noise yet allows warning signals and voices to be clearly understood.

Contains metal material making it easy to trace Reusable, makes the product very cost effective



## **Disposable Earplugs Dispenser**

Easy-to-use, robust dispenser can be either wall-mounted or used on a flat counter. Easy installation equipped with a controlled release mechanism which ensures that the correct number of plugs are dispensed. The audible "1/2 click" system prevents over supply thus reducing wastage costs. The transparent design makes it easy to monitor the number of plugs remaining in the dispenser. A collecting tray catches the earplugs. Installed in a convenient location the dispenser has sufficient capacity to supply large production areas with hearing protection at a favorable price.

Model:	NP100
Color:	Black- Clear container
Packaging:	1 unit box (Earplugs not included)

<b>FEATURES</b> Wall mounted dispenser	
Simple "1/2 click"	
Simple refilling	
Hygienic refilling	

Foam Earplugs suitable for refilling

Simple to use
Earplugs easily accessible for everyone
Simple "click" reliably dispenses
2 earplugs

The holder is transparent so it is easy
to see when it is time to refill
The dispenser holds 300 pairs of plugs
when refilled
Packed in a box
Available in different colors and shapes
for dispenser refilling

**ADVANTAGES** 

Easy to assemble

BENEFITS

Easy to mount on a wall
Can be strategically placed for
users access
Convenient and simple for the user.
Less waste, protects the
environnement
Convenient
Plugs are always available for users
Convenient, Hygienic, Saves valuable
time
Simple to open and fill the dispenser
with the right earplugs



## Refill Packs for Earplug Dispenser

The dispenser can be filled with the following DYNAMIC foam earplugs: NP101/300 and NP102/250. The refill boxes are made of environmentall friendly cardboard which can be recycled to reduce waste.

Model:	NP101/300
Color:	Red - Cordless
Packaging:	300 pairs of "Dyna-Fit" model NP101 loose in a refill box
	4 box of 300 pairs per case

Model:	NP102/250
Color:	Orange - Cordless
Packaging:	250 pairs of "Dyna-Fit Lite" model NP102 loose in a refill box
	4 box of 250 pairs per case



# Hygiene Storage Box for Reusable Earplugs

A sturdy, transparent plastic case, comes with a chain for storing earplugs safely and hygienically.

Model:	NPCASE
Color:	Transparent
Packaging:	60 units per inner box 10 inner boxes per case



# **Banded Ear Protection**"Lite-Band"

MEETS ANSI S3.19-1974 REGULATION & CANADIAN CLASS A(L) STANDARDS

Innovative and unique, soft, oval shape foam earplug guarantee of the most comfortable fit. The band is ergonomically shaped and its stability limits contact

with clothing and resulting sound transmission. The DYNAMIC "LIGHT-BAND" is the lightest banded ear protector available in the market. Weighs just 8 gr.

Ideal for short jobs, for people moving in and out of noise areas or for visitors.

Model:	NP105
Color:	Black band Lime-Green pods
Packaging:	1 per bag 10 per inner box 10 inner boxes per case
Model:	NP105/5
Color:	Lime-Green pods
Packaging:	Pack of 5 pairs of replacemen Pods for NP105



SNR: 24 dB			H: 2	27 dB	M: 1	19 dB	L: 18 dB	
Frequency Hz	63	125	250	500	1000	2000	4000	8000
Mean Attenuation dB	23.7	22.0	21.6	19	23.9	31.9	39.6	39.6
Standard Deviation dB	4	2.9	4.7	4.3	3.6	4.0	2.7	3.7
Assumed Protection dB (APV)	19.7	19.1	16.9	14.7	20.2	27.9	36.9	35.9

NRR: 20 dB			CS	SA Class A	(L) Standar	ds / ANSI	S3.19-197	4 Regulati	ons
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000
Mean Attenuation dB	27.5	28.1	24.5	25.6	32.3	38.8	41.2	44.6	44
Standard Deviation dB	5.7	4.7	3.7	3.9	3.5	4	4.5	4.6	4.6
Assumed Protection dB (APV)	16.1	18.7	17.1	17.8	25.3	30.8	32.2	35.4	34.8

FEATURES
Banded ear plugs
Ear plugs with an oval cap shape
Low weight
LOW Weight
Replacement pods

#### **ADVANTAGES**

Ergonomic pre-formed band Positioned under the chin Perfect fit

Oval cap shape of the plug fits well over the ear canal.

Low weight makes the bands comfortable to wear

Easy to change when they are worn or dirty.

#### **BENEFITS**

Light, comfortable and secure fit Fixed position with reduced sound transmission.

Good fitting without pressure Excellent stability once fitted

Easy fitting, comfortable to wear for long periods.

Hygienic Economic

Ideal for in and out of factory jobs, visitors, foreman or supervisors, light manufacturing, etc.

## **≫SPITFIRE**

# "Spitfire" Plastic Headbanded Earmuff

MEETS ANSI S3.19-1974 REGULATIONS & CSA CLASS A STANDARDS

Combining lightweight and performance

- Dielectric
- Padded headband
- · Adjustable height
- Lightweight

- Comfortable
- Good attenuation



NP111	Clas	Class A							NNR: 24 dB		
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation dB	16.7	20.0	31.4	38.4	36.3	37.5	37.6	37.0	35.1		
Standard Deviation dB	2.8	2.7	3.0	3.2	2.5	3.6	3.2	2.9	1.9		

# **≈**SPITFIRE

# "Spitfire" Plastic Cap-Mounted Earmuff

MEETS ANSI S3.19-1974 REGULATIONS & CSA CLASS A STANDARDS



- Dielectric
- Adjustable height
- Lightweight
- Comfortable

- Good attenuation
- Adjustable arm tension
- Parking position



NP112	Clas	Class A							NNR: 20 dB		
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation dB	15.8	17.3	23.2	30.6	33.9	35.9	36.9	38.5	38.6		
Standard Deviation dB	3.0	2.6	3.6	3.5	3.4	4.0	3.0	3.8	3.8		

## pproxHERCULES

## "Hercules" Plastic **Headbanded Earmuff**

**MEETS ANSI S3.19-1974 REGULATIONS** & CSA CLASS A(L) STANDARDS

Very good performance earmuffs with very good adjustability

- Dielectric
- Padded headband
- Adjustable height
- Soft sealing cushions
- Large size ear-cups
- · High-Visibility ring color
- Comfortable
- Very good attenuation



NP113	Clas	Class AL							
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000
Mean Attenuation dB	21.2	21.9	32.3	40.1	36.7	38.5	41.9	40.7	39.3
Standard Deviation dB	2.9	2.3	2.8	2.7	2.8	2.8	2.8	2.0	2.2

# >HERCULES

## "Hercules" Plastic **Cap-Mounted Earmuff MEETS ANSI S3.19-1974 REGULATIONS** & CSA CLASS A STANDARDS

Very good performance earmuffs with very good adjustability

- Dielectric
- Adjustable height
- Soft sealing cushions
- Large size ear-cups
- · High-Visibility ring color
- Comfortable
- Very good attenuation
- · Multiple parking positions



NP114	Class A							NNR:	NNR: 25 dB		
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation dB	19.9	22.1	30.5	39.7	37.0	37.4	40.3	41.3	37.9		
Standard Deviation dB	3.8	3.2	3.5	3.1	3.1	3.3	4.0	3.6	3.5		

# "Mirage" Wire Headbanded Earmuff

MEETS ANSI S3.19-1974 REGULATIONS & CSA CLASS A(L) STANDARDS

Good performance earmuffs with low profile design

- Metal headband wires for micro-adjustment
- · Padded headband
- Adjustable height
- · Low profile ear-cups
- Very comfortable

- Very good attenuation
- Also available in neck-mounted version (NP120)
  - Widely used with welding shields (see page 17)

NP115	

**MIRAGE** 

NP115	Class AL							NNR: 25 dB		
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000	
Mean Attenuation dB	21.2	21.9	32.3	40.1	36.7	38.5	41.9	40.7	39.3	
Standard Deviation dB	2.9	2.3	2.8	2.7	2.8	2.8	2.8	2.0	2.2	

## **≫MIRAGE**



# "Mirage" Cap-Mounted Earmuff

MEETS ANSI S3.19-1974 REGULATIONS & CSA CLASS A STANDARDS

Good performance earmuffs with low profile design

- Adjustable height
- Low profile ear-cups
- · Very comfortable

- · Very good attenuation
- Crown parking position

NP116	Clas	Class A							NNR: 23 dB		
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation dB	14.9	18.4	25.8	32.7	36.3	37.3	36.7	36.2	35.7		
Standard Deviation dB	2.2	2.4	2.2	2.9	3.2	3.7	3.2	3.4	3.6		

### **≫B52**



# "B52" Wire Headbanded Earmuff

MEETS ANSI S3.19-1974 REGULATIONS & CSA CLASS A(L) STANDARDS

High-performance earmuffs without compromising comfort

- Metal headband wires for micro-adjustment
- Padded headband
- Adjustable height
- Large soft sealing cushions
- Extra-large size ear-cups
- Extremely comfortable
- Excellent attenuation

NP117	Clas	Class AL							NNR: 28 dB		
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation dB	20.0	23.7	33.7	37.6	35.5	39.9	42.4	44.2	43.6		
Standard Deviation dB	2.7	2.1	2.9	2.7	2.2	3.4	3.0	2.1	2.8		

## **≈**B52



# "B52" Cap-Mounted Earmuff

MEETS ANSI S3.19-1974 REGULATIONS & CSA CLASS A STANDARDS

High-performance earmuffs without compromising comfort

- · Adjustable height
- Large soft sealing cushions
- Extra-large size ear-cups
- Extremely comfortable
- Excellent attenuation
- Crown parking position

NP118	Class A								NNR: 25 dB		
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation dB	19.1	21.7	30.7	36.3	39.4	36.8	31.8	34.8	35.5		
Standard Deviation dB	3.8	2.6	1.9	3.8	1.8	3.6	2.4	1.8	3.4		



# "Piper" Plastic Headbanded Earmuff

MEETS ANSI S3.19-1974 REGULATIONS & CSA CLASS B STANDARDS

Lightweight and economic

- Dielectric
- Adjustable height
- Lightweight

- · Easy to adjust
- Great value

NP110	Class B							NNR: 24 dB		
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000	
Mean Attenuation dB	8.7	18.4	30.7	51.7	42.4	39.8	40.7	39.5	38.7	
Standard Deviation dB	0.4	0.7	0.2	0.5	0.9	0.5	3.7	1.8	1.4	

## **≫BUFFALO**



## "Buffalo" Wire Cap-Mounted Earmuff

MEETS ANSI S3.19-1974 REGULATIONS & CSA CLASS A(L) STANDARDS

Good-performance earmuff with good fit

- Metal wires for micro-adjustment
- Specially designed for wide-brim hard hats
- Adjustable height
- · Large soft sealing cushions
- Large size ear-cups
- Very comfortable
- · Very good attenuation

NP119	Class AL								NNR: 26 dB		
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation dB	20.8	22.5	31.9	36.5	40.0	39.8	32.2	34.9	35.7		
Standard Deviation dB	3.7	2.0	2.8	2.6	3.2	3.2	2.2	2.2	3.6		

## **≈MIRAGE**

# "Mirage" Neck-Mounted Earmuff

MEETS ANSI S3.19-1974 REGULATIONS & CSA CLASS A STANDARDS

Good performance earmuffs with low profile design

- Adjustable height
- Low profile ear-cups
- Very comfortable

- Very good attenuation
- · Widely used with welding shields



NP120	Class A							NNR: 24 dB		
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000	
Mean Attenuation dB	15.3	19.6	27.9	35.3	35.9	40.5	42.2	41.9	41.5	
Standard Deviation dB	2.4	2.5	2.9	3.4	2.2	2.4	3.6	2.4	4.1	

## *<b>∼***CONCORDE**



# "Concorde" Wire Foldable Headbanded Earmuff

MEETS ANSI S3.19-1974 REGULATIONS & CSA CLASS A STANDARDS

Lightweight with good performance

- Metal headband wires for microadjustment
- Padded headband
- Adjustable height
- Lightweight

- Easy to store
- Very comfortable
- Good attenuation

NP121	Class A							NNR: 25 dB		
Frequency Hz	125	250	500	1000	2000	3150	4000	6300	8000	
Mean Attenuation dB	16.0	20.3	29.6	37.3	36.0	40.2	41.3	42.5	41.7	
Standard Deviation dB	2.8	2.2	2.7	2.8	2.3	3.0	3.3	2.2	3.1	





# DE LUXE FORESTERY AND GARDENING KIT NPK10

Kit:

NPK10

(1) HP542R-01 Class 2 White Safety Hat, (1) EPB101 Plastic Faceshield Bracket, (1) EPWM815 Metal Forestry Screen Visor,

(1) NP118 "B52" EarMuff.



# QUALITY FORESTERY AND GARDENING KIT NPK11

Kit:

NPK11

(1) HP241R02 Class 1 Yellow Safety Hat, (1) EPB101 Plastic Faceshield Bracket, (1) EPWM815 Metal Forestry Screen Visor,

(1) NP116 "Mirage" Ear Muff.



#### GOOD GARDENING KIT NPK12

Kit:

NPK12

(1) HP241-04 Class 1 Dark Green Safety Hat, (1) EPB101 Plastic Faceshield Bracket, (1) EPWM815 Metal Forestry Screen Visor, (1) NP112 "Spitfire" Ear Muff.



#### **INDUSTRIAL KIT** NPK13

Kit:

(1) HP241R-01 Class 1 White Safety Hat, (1) EPB101 Plastic Faceshield Bracket, (1) EP815/40 PETG Clear Faceshield,

(1) NP116 "Mirage" Ear Muff.



#### **DE LUXE KIT** NPK14

Kit:

(1) HP142R-15 Class 2 Red Safety Hat, (1) EPB103 Faceshield Bracket, (1) EPWM815 Metal Forestry Screen Visor, (1) NP118 "B52" EarMuff.

For Pricing and Availability Call 1-800-561-3600 or email info@bapequipment.